

# LifeSize® Phone™ 2nd Generation

# **HD Video Collaboration at Your Fingertips**

LifeSize® Phone™ puts the power to control both HD video and audio collaboration at your fingertips. The phone features an intuitive touch-screen interface so simple that anyone can use it. And it's so engaging that everyone will want to use it. No longer do you need a separate remote control to manage your call. The intuitive touch-screen interface of the LifeSize Phone makes video communication effortless. Users can share content, control cameras, change layouts, add callers and more with ease.

When you collaborate over video, your video conferencing technology should be so intuitive that it feels natural to use. Now you can have confidence managing your video and audio conferencing technology with the LifeSize Phone. It's easier than ever to make calls and collaborate with colleagues and partners.

#### **Best-in-Class Audio Quality**

The touch-screen simplicity of the LifeSize Phone combines with superior audio quality to deliver an engaging video communication experience and more productive video calls. Advanced beam-forming technology steers microphones to the location of the speaker and reduces room noise. That means everyone in the conference room can be heard, no matter where they are sitting. There's no need to huddle over the phone or move the phone during calls.

Best-in-class frequency response is achieved through a powerful loudspeaker driver in a large, acoustically suspended speaker enclosure, which reduces distortion and makes voices and conversations more true to life. It's as if callers are sitting across the table from each other.

#### **A Total Conference Room Solution**

The new LifeSize Phone is currently available exclusively with LifeSize® Room 220™, which includes a codec, LifeSize® Camera 10x™ and LifeSize Phone—delivering an unparalleled conference room experience.

Touch-screen simplicity. Best-in-class audio quality. LifeSize Phone will change your conference room experience and elevate the conversation for everyone!



Now with touch-screen simplicity

## LifeSize Phone Key Features

Simple to use

The intuitive touch-screen interface is so simple anyone can use it

Optimized for video communication

The first touch-screen conference phone to enable both video and audio management

Simplified operation

Context-sensitive UI reduces on-screen clutter

Flexible set up

Power over Ethernet (PoE) enabled and requires only one cord for set up

Greater voice pickup and clarity

360-degree microphone array with advanced beam-forming technology provides total room coverage

Best frequency response

90 Hz to 16 kHz delivers natural voice reproduction

LifeSize Phone. Elevate the conversation.

### **Product Specifications**

## LifeSize® Phone™ 2nd Generation

#### **Phone Console Specifications**

#### System Speaker

Powerful rare-earth magnet loudspeaker driver Large, acoustically suspended speaker enclosure Frequency response: 90 Hz to 16 kHz for deep voice reproduction plus high intelligibility without hiss Volume adjustable to 90 dB SPL at ½ meter peak Distortion at -10 dBmO

<3% 100 Hz-200 Hz, <0.5% 250 Hz-20,000 Hz

Spectral peak limiting prevents speaker clipping without distortion

#### **System Microphones**

Four orthogonally placed low-noise microphones (80 dB SNR before noise reduction)

Beam-former algorithm steers the microphones to the location of the talker for greater voice pickup and reduced room noise

#### **Advanced Audio Features**

Acoustic echo cancellation
Microphone background noise suppression
VAD (Voice activity detector)
AGC (Microphone automatic gain control)
Adaptive jitter buffers and packet loss concealment
Pro-audio 48 kHz sampling rate

#### **Touch-Screen Display**

WQVGA capacitive multi-touch display Size: 4.3 inch (Diagonal) Resolution: 480 x 272 pixels, 0.198 mm pitch (128 PPI) Contrast: 500:1 (typical) Max brightness: 500 cd/m² (typical)

#### Network

VoIP connectivity and video systems integration in one device

Ethernet connection: Shielded RJ-45 connector 10/100 Mbps auto-sensing

Auto-MDIX

Half or full duplex

Link/activity LED indicator

PoE power LED indicator

4 high-speed digital LifeSize Link connectors for future devices

#### No Mobile Device Interference

Designed to reduce or eliminate audible radio frequency interference when mobile devices are placed adjacent to LifeSize Phone

#### **System Design**

Physical Dimensions Height: 46.5 mm / 1.83 in Diameter: 266 mm / 10.48 in Weight: 1.5 Kg / 3.3 lbs

#### **Power Consumption**

Not in call: 6.5 W In call: 7.6 W

#### **Environmental Data**

Operating temperature:  $0^{\circ}$ C (32°F) to  $40^{\circ}$ C ( $104^{\circ}$ F) Operating humidity: 10% to 85%, non-condensing Storage temperature:  $-20^{\circ}$ C ( $-4^{\circ}$ F) to  $60^{\circ}$ C ( $140^{\circ}$ F) Storage humidity: 10% to 90%, non-condensing

#### LifeSize Phone Package

Tabletop console

Cables: 1 - 30 ft. (9.14m) RJ-45 cable for connection to LifeSize video system

Power over Ethernet (PoE) enabled, 802.3af LifeSize Phone, 2nd Generation = Regulatory model LFZ-021

#### For additional information:

www.lifesize.com/support

Information contained in this document is subject to change without notice.





#### AMERICAS:

1601 S. MoPac Expressway Suite 100 Austin, Texas 78746 USA

Phone +1 512 347 9300 Toll Free +1 877 543 3749 www.lifesize.com

#### EMEA:

LifeSize Regional Office 49 89 20 70 76 0 (Germany) Toll Free Europe 00 8000 999 09 799

#### APAC:

LifeSize Regional Office +65 6303 8370 (Singapore)